# **OVERVEIW AND OPERATION PROCESS**

# 1. FUEL SYSTEM SPECIFICATION

## ▶ Use Only Unleaded Fuel Rated at 89 Octane or Higher

Fuel quality and additives contained in fuel have a significant effect on power output, drivability, and life of the engine. Fuel with too low an octane number can cause engine knock.



#### CAUTION

- Use of fuel with an octane number lower than 89 may damage engine and exhaust system.



#### CAUTION

- To prevent accidental use of leaded fuel, the nozzles for leaded fuel are larger, and will not fit the fuel filler neck of your vehicle.

#### ▶ Do Not Use Methanol

Fuels containing methanol (wood alcohol) should not be used in vehicle.

This type of fuel can reduce vehicle performance and damage components of the fuel system.



### CAUTION

- Use of methanol may damage the fuel sys-tem.

### ▶ Vehicle Fueling from Drums or Storage Containers

For safety reasons (particularly when using noncommercial fueling systems) fuel containers, pumps and hoses must be properly earthed. Static electricity build up can occur under certain atmospheric and fuel flow conditions if unearthed hoses, particularly plastic, are fitted to the fuel-dispensing pump.

It is therefore recommended that earthed pumps with integrally earthed hoses be used, and that storage containers be properly earthed during all noncommercial fueling operations.

Modification basis	
Application basis	

Affected VIN



# ► Temperature vs resistance

96	°F	ECT Sensor	IAT Sensor	
°C	1	ohms (Ω)		
	Temperature vs Resistand	ce Values (Approximate)		
130	266	88	102	
120	248	111.6	127	
110	230	143	159	
100	212	202	202	
90	194	261	261	
80	176	340	340	
70	158	452	452	
60	140	609	609	
50	122	835	835	
40	113	1166	1166	
30	86	1662	1662	
20	68	2420	2420	
10	50	3604	3604	
0	32	5499	5499	
-10	14	8609	8609	
-20	-4	13850	13850	
-30	-22	22960	22960	
-40	-40	39260	39260	

Modification basis	
Application basis	
Affected VIN	